

stop crime fast with the

# SENTINEL S55 v6

COMPACT | EFFECTIVE | VERSATILE | ECONOMICAL



sen-ti-nel n. A guard whose job is to stand and keep watch

**Suitable for a  
wide range of  
applications**

**Quality assured  
performance  
and reliability**

**Simple  
installation and  
integration**

The Smoke Screen Sentinel range has been designed and manufactured for permanent installation either as a fully integrated part of an intruder alarm system or as a stand-alone system. The range comprises some of the most advanced security smoke generators in the world.

The new, precision engineered heater block offers high performance levels and reliability. This translates to a more impressive volume of drier fog (no residue) that lasts for even longer.

The Sentinel S55 boasts a new feature called Turbo Mode providing maximum protection in risk critical areas. It has a minimum off-mains capability of 40 minutes giving you peace of mind should you encounter power difficulties.

The latest electronics pack provides the facility to add on a IOT daughter card allowing integration with a myriad of control systems. Other features such as the internal battery back-up and enough fluid capacity make the S55 incredibly versatile.



---

## ‘ANTI-RAID’ FIRST BURST

Re-engineered Turbo mode for maximum smoke generation in risk critical areas designed to stop thieves in their tracks.

---

## VERSATILITY IS KEY

Compact and inexpensive, suitable for private homes, server rooms, small offices, stores, window displays and more.

---

## MULTI-NOZZLE OPTIONS

A range of different nozzles are available to produce a range of different effects. This makes installation even easier.

---

### FEATURES

- 1-year parts and labour warranty & a further 24 months parts only warranty.
- Full heater redundancy protects against critical failure.
- Turbo mode for maximum smoke generation in risk critical areas.
- 35 second initial burst for maximum smoke generation in risk critical areas.
- Min. 40 minutes off-mains operational capability.
- Energy save mode cuts costs in periods when the generator is not immediately needed.
- IP interface available.
- Supports automatic re-firing via screen-sensor technology.
- Extreme temperature operation: -10°C to 50°C.
- £10 million product and public liability insurance.

### OPERATION

- 5 inputs and 7 outputs.
- LCD status display and on-board event log.

### CONSTRUCTION

- Rugged and compact steel casing in white/black.
- Environmental pack for installation in confined spaces with elevated ambient temperatures.

### STANDARDS COMPLIANCE

- EN50131:8 grade II and IEC62642-8.
- CNPP Rating: Class I Category 30.

### FLUID

- 1000ml Swift Fit bottle.

### DATA

- 36.8(H) x 13.8(D) x 23.1(W) cm.
- Weight: 12 kg (pre-install), 17 kg (installed).

# CAN'T SEE IT? CAN'T STEAL IT!