

TIS ZIGBEE GATEWAY

ZIGBEE-BUS RS485 CONVERTER

Data Sheet Rev 3.1

Model: TIS-ZIG-PORT





OVERVIEW

The Zigbee Gateway is a programming and communication gateway used to integrate Zigbee 3.0 devices with TIS BUS RS485. This device helps to limitlessly create an all-connected network of smart devices with an advanced functionality to cover every details in the room.

KEY BENEFITS

- Programming and Communication Port
- TIS Cloud Server Connection
- Zigbee 3.0 Protocol Controller

KEY FEATURES

- Standard 35 mm Din-Rail Mounted
- Support 128 Zigbee zones
- ★ Works with TIS-BUS Protocol









TIS ZIGBEE GATEWAY



ZIGBEE-BUS RS485 CONVERTER Model: TIS-ZIG-PORT

PRODUCT SPECIFICATIONS			
(Ports	Zigbee RS485 RJ45	Zigbee 3.0 TIS-BUS Ethernet UDP - TCP/IP connection
TISBUS	TIS Bus	Number of devices on 1 line Bus voltage Current consumption Protection	Max. 64 12-32 V DC <40 mA / 24 V DC Reverse polarity protection
()	Reaction time	approx. 20ms	
Q o	Function programmable options	Zigbee 3.0 Ethernet Rj45 Upgrading PRG button	Program 128 channel UDP TIS Protocol – TCP/IP TIS Claude By UDP Ethernet port To rest IP address to 192.168.10.100 (default)
Ø.	Mounting	Din Rail Wall mount	Standard 35 mm Din rail screw holder on the back of the module
۵	Weight	Without packaging	0.21 KG
	Dimensions	Width \times length \times height	90mm × 73mm × 76mm
	Connection terminal	Load and Power Data / bus	Screw terminal 0,254mm2 Male/female connectors Link + screw Terminal
+	Housing	Materials Casing color IP rating	ABS anti fire Black Gray IP 20
	Temperature range	Operation Storage Transport	-3060°C -2060°C -3075°C
8	Air humidity		<85% non-condensing





