

DH-PFM972-6U-1/2/3

1m/2m/3m UTP CAT6 RJ45 Patch Cord



Features

- · CAT6 with RJ45 connectors
- · Made of 99.97% oxygen free copper
- · PVC sheath, safe and environmentally friendly

Overview

The network patch cord is standard RJ45 interface patch cord suitable for users and information points in the work area or equipment and patch panels in the management room.

Technical Specification		
Model	DH-PFM972-6U-1/2/3	
Conductor		
Material	OFC(99.97% copper)	
Gold Plating Thickness	$3\mu\text{in}$ (0.0762 $\mu\text{m})$ of gold and $80\mu\text{in}$ (2.032 $\mu\text{m})$ of nikel	
Diameter	24AWG 4P	
Structure	7*0.20mm±0.01mm(7*0.007"±0.0004")	

Generic Cabling | DH-PFM972-6U-1/2/3

Insulation				
Material	HDPE			
Diameter	0.9mm±0.05mm(0.03"±0.0019")			
Color	Blue-white/blue, orange-white/orange, green-white/green, brown-white/brown			
Elongation at break	≥100%			
Strippability	No damage to insulation and conductors			
Separator				
Separator	Yes			
Sheath				
Material	PVC			
Diameter	6.0mm±0.40mm(0.23"±0.0157")			
Color	Yellow, blue, gray			
Tensile Strength	≥9MPa			
Elongation At Break	≥100%			
Structure				
Cable Length	1m/2m/3m(3.28ft/ 6.56ft/9.84ft)			
Wire Diameter	24 to 26 AWG			
Plug and unplug times	>750 times			
Working temperature	-20°C to +70°C (-4°F to 158°F)			
Packaging Method	1m: 1pc in 1 bag, 120 bags in 1 box 2m: 1pc in 1 bag, 90 bags in 1 box 3m: 1pc in 1 bag, 60 bags in 1 box			
Packaging Dimension	410mm×270mm×380mm(16.14"×10.62"×14.96")			
Gross Weight	3m: 130g(286.60lb) 2m: 93g(205.02lb) 1m: 55g(121.25lb)			

Ordering Information				
Туре	Model	Description		
UTP CAT6 RJ45 Patch Cord	DH-PFM972-6U-1	1m UTP CAT6 RJ45 Patch Cord ; Yellow/blue/gray		
	DH-PFM972-6U-2	2m UTP CAT6 RJ45 Patch Cord ; Yellow/blue/gray		
	DH-PFM972-6U-3	3m UTP CAT6 RJ45 Patch Cord ; Yellow/blue/gray		

