

OS-PTZ-H4EN30-ALT | 4MP 30X IR PTZ HDCVI CAMERA



HDCVI

- 1/3" 4Megapixel CMOS
- Powerful 30x optical zoom
- 120dB true WDR, 3D DNR
- Max. 25/30fps@4M/1080P, 25/30/50/60fps@720P
- IR distance up to 100m
- IP66



System Overview

Featuring with powerful optical zoom and accurate pan/tilt/zoom performance, the OS-PTZ-H4EN30-ALT series PTZ camera can provide large monitoring range and great detail. The camera delivers 4MP resolution at 25/30 fps, with 30x optical zoom. OS-PTZ-H4EN30-ALT series PTZ is equipped with smooth control, high quality image and good protection, which make it can meet most of the requirements of video surveillance applications.

Functions

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Wide Dynamic Range

Embedded with industry leading wide dynamic range (WDR) technology, vivid pictures are achieved even in the most intense contrast lighting conditions. True WDR (120dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Environmental

With a temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments. Subjected and certified to rigorous dust and water immersion tests, the IP66 rating makes it suitable for demanding outdoor applications.

Protection

This camera suits even the harsh conditions for outdoor applications. Its 6KV lightning rating provides protection against the camera and its structure from the effects of lightning.

OS-PTZ-H4EN30-ALT | 4MP 30X IR PTZ HDCVI CAMERA







Technical Specifications

Camera			
Image Sensor	1/3" CMOS		
Effective Pixels	2592(H) x 1520(V), 4 Megapixels		
Scanning System	Progressive		
Electronic Shutter Speed	PAL: 1/3s~1/30,000s NTSC: 1/4s~1/30,000s		
Minimum Illumination	Color: 0.05Lux@F1.6; 0Lux@F1.6 (IR on)		
S/N Ratio	More than 55dB		
IR Distance	Distance up to 100m (328ft)		
IR On/Off Control	Auto/Manual		
IR LEDs	6		
Lens			
Focal Length	4.5mm~135mm		
Max. Aperture	F1.6 ~ F4.4		
Angle of View	H: 60° ~ 2.2°		
Optical Zoom	30x		
Focus Control	Auto/Manual		
Close Focus Distance	100mm~ 1000mm		
Dori Distance			
*Note: The DORI distance is a “general proximity” of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.			
Detect	Observe	Recognize	Identify
2700m (8858ft)	1080m (3543ft)	540m (1772ft)	270m (886ft)
PTZ			
Pan/Tilt Range	Pan: 0° ~ 360° endless Tilt: -15° ~ 90° auto flip 180°		
Manual Control Speed	Pan: 0.1° ~160° /s; Tilt: 0.1° ~120° /s		
Preset Speed	Pan: 240° /s; Tilt: 200° /s		
Presets	300		
PTZ Mode	5 Pattern, 8 Tour, Auto Pan, Auto Scan		
Speed Setup	Human-oriented focal length/ speed adaptation		
Power up Action	Auto restore to previous PTZ and lens status after power failure		
Idle Motion	Activate Preset/ Scan/ Tour/Pattern if there is no command in the specified period		
Protocol	DH-SD, Pelco-P/D (Auto recognition)		



Video	
Resolution	4M(2592x1520) / 1080P(1920x1080) / 720P(1280x720)
Frame Rate	25/30fps@4M/1080P, 25/30/50/60fps@720P
Video Output	1-channel BNC high definition video output/ CVBS standard definition video output (switchable)
Day/Night	Auto(ICR) / Color / B/W
OSD Menu	Support
Backlight Compensation	BLC / HLC / WDR (120dB)
White Balance	Auto,ATW,Indoor,Outdoor,Manual
Gain Control	Auto / Manual
Noise Reduction	Ultra DNR (2D/3D)
Digital Zoom	16x
Flip	180°
Privacy Masking	Up to 24 areas
Certifications	
Certifications	CE: EN55032/EN55024/ EN50130-4 FCC: Part15 subpartB,ANSI C63.4- 2014 UL: UL60950-1+CAN/CSA C22.2,No.60950-1
Interface	
Video Interface	1
Audio Interface	1 channel in
RS485	1
Alarm I/O	1/2
Electrical	
Power Supply	AC24V/3A(±10%)
Power Consumption	13W,23W (IR on)
Environmental	
Operating Conditions	-40°C ~ 60°C (-40°F ~ +140°F) / Less than 95% RH
Ingress Protection	IP66
Vandal Resistance	N/A
Construction	
Casing	Metal
Dimensions	ø205(mm) x 336(mm)
Net Weight	5kg(11.02lb)
Gross Weight	8.3kg(18.30lb)

OS-PTZ-H4EN30-ALT | 4MP 30X IR PTZ HDCVI CAMERA

Mounting options

Junction Mount PFA114 + PFB303W + PFA120	Pole Mount PFA114 + PFB303W + PFA150	Corner Mount PFA114 + PFB303W + PFA151
		
Power Box Mount PFA114 + PFB303W + PFA140	Ceiling Mount PFA114 + PFB300C	Parapet Mount PFA114 + PFB303S
		


Accessories (included)

Wall Mount 64FB	Power Supply AC24V/3A
	

Accessories (optional)

Mount adapter PFA114	Wall Mount PFB303W	Power Box PFA140
		
Ceiling Mount PFB300C	Junction Box PFA120	Pole Mount PFA150
		
Corner Mount PFA151	Parapet Mount PFB303S	
		

Dimensions (mm/inch)



* The information contained in this document (photos, drawings, dimensions, specifications) may be subject to change without prior notice.
 ** Copyright© Osiris Security. All rights reserved. The information in this document can not be published, rewritten or republished in any form. If you wish to use the text or images in this document for commercial reasons, please contact marketing@osiris-security.com