

CONTROL PANELS

JA-100K
JA-100KR

JA-103K-7Ah
JA-103KR

JA-103K
JA-103KR

JA-107K
JA-107KR

SYSTEM DEVICES

COMMUNICATORS

JA-190X*
JA-191Y*
JA-190Y*
JA-192Y
JA-194Y

RADIO MODULES

JA-111R
PLV-JA111R
JA-111R 80

ACCESSORIES

JA-150R
JA-120Z
JA-110Z
JA-110T
JA-121T

SIRENS

INTERNAL

JA-110A
JA-110A II

EXTERNAL

JA-150A II
JA-163A -BASE-RB
JA-152A

JA-1X1A-C-ST /-B
JA-1X1A-C /-WH /-AN /-GR
JA-1X1A-C /-WH-B /-AN-B /-GR-B

ACCESS MODULES

INTERNAL

JA-112E
JA-113E /-AN /-GR /-WH
JA-114E /-AN /-GR /-WH
JA-110E

JA-192E /-AN /-GR /-WH
JA-153E /-AN /-GR /-WH
JA-154E /-AN /-GR /-WH
JA-150E

EXTERNAL

JA-120E-WH /-BK
JA-121E-WH /-BK
JA-122E
JA-123E

ENVIRONMENTAL DETECTORS

INTERNAL

GAS LEAK

EI208W
EI208DW
GS-133

FLOOD

JA-110F
LD-12
LD-81

SMOKE AND HEAT

JA-110ST
JA-111ST-A

JA-150ST
JA-151ST
JA-151ST-A

THERMOMETERS AND THERMOSTATS

JA-111TH
JA-110TP

JA-151TH
JA-150TP

EXTERNAL

JA-110G-CO
JA-150G-CO

THERMOMETERS

JB-EXT-TH-B
JB-EXT-TH-R

REMOTE CONTROLS AND EMERGENCY DEVICES

REMOTE CONTROLS

JA-152J MS II
JA-154J MS II
JA-155J

EMERGENCY DEVICES

JA-112J
JA-188J
JA-158J
JA-159J
JA-157J
JA-156J

DETECTORS

INTERNAL

MOTION

JA-110P
JA-110P PET
JA-112P (G)
JA-115P

JA-150P
JA-150P PET
JA-152P (G)
JA-155P

JA-186P

VERIFICATION

JA-120PC
JA-120PC (90)

JA-160PC
JA-160PC (90)

COMBINED AND DUAL

JA-122PW (G)
JA-120PW
JA-120PB

JA-162PW (G)
JA-180W
JA-180PB

BUILDING PERIMETER

JA-111M /B /-AN /-GR
JA-112M
JA-111SH
JA-110B

JA-151M /B /-AN /-GR
JA-150M /B /-AN /-GR
JA-182SH
JA-180B

JA-152M
JA-182M
JA-152SHM

EXTERNAL

MOTION

JA-158P
JA-159P
JA-157P
JA-169P

OPTICAL

JA-150IR
JA-151IR

MODULES

INPUT

JA-111H TRB
JA-111H -AD TRB

JA-114HN
JA-116H
JA-118M

OUTPUT

JB-110N
JB-118N
JB-111N

JA-150N
JA-151N

JB-150N -HEAD
JB-160N -PLUG
JB-161N -PLUG

AC-160 -DIN
AC-160-C

JA-110N -DIN
JA-112I

JA-150EM -DIN
JA-111I

NEW PRODUCTS

in **JABLOTRON 100+** portfolio

Alarm with intuitive control

JABLOTRON 100+

PRODUCT MAP | 2023

JA-103K-7Ah Control panel

- Max. no. of sections 8
- Max. no. of users 50
- Backup battery 12V / 7Ah

JA-169P Outdoor two-zone PIR motion detector

- Ingress Protection IP45
- Detection characteristics 15 m / 85°
- Max. radio-frequency output 25 mW
- Max. power consumption 55 mA

JA-113E, JA-114E JA-153E, JA-154E Access modules

- Colour variants -AN/ -GR /-WH

JA-120E-WH /-BK JA-121E-WH /-BK Touch access modules

- Ingress Protection IP55
- RFID frequency 125 kHz
- MIFARE frequency 13,56 MHz
- Max. power consumption 105 mA

JA-152SHM Wireless shock or tilt detector with a magnetic contact

- Max. radio-frequency output 18 mW
- Max. power consumption 80 mA

JB-160N-PLUG (French) JB-161N-PLUG (Schuko) Smart plugs

- Max. radio-frequency output 25 mW
- Resistive load (cos φ = 1) max. 16 A

JA-111M, JA-151M JA-150M Magnetic detectors

- Colour variants B /-AN /-GR

-  BUS devices
-  WIRELESS devices



www.jablotron.com

C-EN+MAP23011

EN
50131

2
GRADE

JABLOTRON
CREATING ALARMS